

Erect Type GJS08E3

Description:

The GJS08E3 closure allows three cables in and three cables out.

It accommodates the splicing and branching of the cable which is used in aerial-hanger, wall-mounting or direct buried.

The closure is an openable box which is made from high-quality PC.

The closure and the foundation plate are sealed with silicon Gum Material which fixes tightly by hoop.

The entry ports are sealed by heat-shrinkable tube.

The closure can be opened and used again.



Performance:

- Operating temperature: -40 °C ~ +65 °C
- Storage temperature: -25°C ~ +65°C
- Air pressure: 70Kpa ~ 106Kpa
- Sealing Performance \geq 150Kpa/72h



Maximum Capacity	Splice Tray Model	Splicing Block	Splice Tray Capacity	Max.Splice Tray	Recommended Capacity	Dimension (L×W)	Weight
Bundle 96 cores	SL-158	SL-24	24	4	Bundle 60 cores	530mm×240mm	2.30kg
Bundle 48 cores	SL-160	N/A	12	4	Bundle 48 cores	530mm×240mm	2.30kg
Bundle 64 cores	SL-162	N/A	16	4	Bundle 64 cores	530mm×240mm	2.30kg

Features:

Advanced internal structure design, high-strength engineering plastic ABS

Effectively prevent products from aging caused by coldness, heat, oxygen and ultraviolet radiation

Main components provide fire resistant, waterproof, and quakeproof while protecting splice closure during pulling, torsioning and impacting

Fiber splice tray is designed in SLIDE-IN-LOCK and its opening angle is above 90 degree

Pressure testing valve can be installed as well for pressure testing and sealing testing after injection air

Reliable fastening, stripping and earthing devices for optic fiber

Accessories make fiber avoid damaging

Erect Type GJS08E3

Main Configuration:

Item	Unit	Quantity				Remark
		48Core	60Core	64Core	96Core	
Closure case shell	SET	1	1	1	1	
Supporting frame	PCS	1	1	1	1	
Fiber splice tray	PCS	4	4	4	4	
Fiber splice tray cover	PCS	1	1	1	1	
Sealing gasket	PCS	1	1	1	1	
Lock-sealing device	PCS	1	1	1	1	

Accessory Parts:

Item	Unit	Quantity				Remark
		48Core	60Core	64Core	96Core	
Heat shrink tube	PCS	48	60	64	96	
Cable Heat shrink tube	PCS	6	6	6	6	ø30mm
Protecting Tube	PCS	24	30	32	48	Length=72cm
Nylon Locking Tie	PCS	10	20	20	25	
Branch block	PCS	1	1	1	1	
Wedge	PCS	1	1	1	1	
Hex screwdriver	PCS	1	1	1	1	
Metal supporting device	SET	1	1	1	1	
Cleaning kit	SET	1	1	1	1	
Number Label	SET	1	1	1	1	
Packing List	PCS	1	1	1	1	

Applications:

- Underground
- Aerial
- Duct-mounting