

Description:

The GJS11E3 closure allows three cables in and three cables out.

It accommodates the splicing and branching of the cable which is used in aerial-hanger, wall-mounting or direct buried.

The closure is an openable box which is made from high-quality PC.

The closure and the foundation plate are sealed with silicon Gum Material which fixes tightly by hoop.

The entry ports are sealed by heat-shrinkable tube.

The closure can be opened and used again.



Performance:

- Operating temperature: -40 °C ~ +65 °C
- Storage temperature: -25°C ~ +65°C
- Air pressure: 70Kpa ~ 106Kpa
- Sealing Performance: \geq 150Kpa/72h



SL-174

Maximum Capacity	Splice Tray Model	Splicing Block	Splice Tray Capacity	Max.Splice Tray	Dimension (L×W)	Weight
Bundle 144 cores	SL-174	SL-24	36	4	558mm×298mm	4.5kg
Ribbon 288 cores	SL-174	SL-48	72	4	558mm×298mm	4.5kg

Features:

Advanced internal structure design, high-strength engineering plastic ABS Effectively prevent products from aging caused by coldness, heat, oxygen and ultraviolet radiation.

Main components provide fire resistant, waterproof, and quakeproof while protecting splice closure during pulling, torsioning and impacting.

Fiber splice tray is designed in SLIDE-IN-LOCK and its opening angle is above 90 degree.

Pressure testing valve can be installed as well for pressure testing and sealing testing after injection air.

Reliable fastening, stripping and earthing devices for optic fiber.

Accessories make fiber avoid damaging

▶▶ Fiber Optic Splice Closure

Erect Type GJS11E3



Main Configuration:

Item	Unit	Quantity					Remark
		72Core	108Core	144Core	216Core	288Core	
Closure case shell	SET	1	1	1	1	1	
Supporting frame	PCS	1	1	1	1	1	
Fiber splice tray	PCS	2	3	4	3	4	
Fiber splice tray cover	PCS	1	1	1	1	1	
Sealing gasket	PCS	1	1	1	1	1	
Lock-sealing device	PCS	1	1	1	1	1	

Accessory Parts:

Item	Unit	Quantity					Remark
		72Core	108Core	144Core	216Core	288Core	
Heat shrink tube	PCS	72	108	144	54	72	
Cable Heat shrink tube	PCS	6	6	6	6	6	ø33mm
Protecting Tube	PCS	36	54	72	54	72	Length=72cm
Nylon Locking Tie	PCS	1	1	1	1	1	
Branch block	PCS	1	1	1	1	1	
Wedge	PCS	1	1	1	1	1	
Hex screwdriver	PCS	1	1	1	1	1	
Metal supporting device	SET	1	1	1	1	1	
Cleaning kit	SET	1	1	1	1	1	
Number Label	SET	1	1	1	1	1	
Packing List	PCS	1	1	1	1	1	

Applications:

- Underground
- Aerial
- Duct-mounting